



genesis™

PREFINISHED COMPRESSED FIBRE CEMENT / MANUFACTURED BY FAIRVIEW

SPECIFICATION SHEET

GENESIS COMPRESSED FIBRE CEMENT FACADE SYSTEM

PRODUCT

Manufacturer	FVA Group (Fairview)
System	Genesis
Panel Type	Compressed Fibre Cement
Panel Profiles	Raw, Hewn, Groove, Infuse, Classic, Rustik.
Thickness	8mm - 12mm (as specified on drawings)
Finish	Pre-finished. Variations: through-coloured or acrylic colour coated (optional HR Coating), sanded, semi-transparent coating, sandblasted, grooved, metallic reflectivity.
Colour	Refer to Genesis Product Information brochure.
Panel Size	Standard Genesis panel sizes per manufacturer's data sheet.
Joint Type	8-10mm shadow line EPDM/Aluminium strip
Application	Commercial, Industrial, Residential, Educational and Aged care.

COMPLIANCE REQUIREMENTS

Complies with NCC 2022, Volume 1	<p>Section C – Fire Resistance</p> <p>Non-combustible in accordance with NCC2022 – clause C2D10 (6) (d)</p> <p>Tested to AS1530.3</p> <p>Product Group Number Classification – Group 1 classified</p> <p>Rated to BAL-29 in accordance with AS3959:2018.</p> <p>Section F – Health and Amenity</p> <p>Weatherproof façade system in accordance with AS 4284.</p> <p>Section B – Structure</p> <p>Structural design specification in accordance with AS/NZS 4600 and AS/NZS1170.</p>
Durability	50+ years design life; termite/rot/mildew resistant
Certification	CodeMark certified when installed in full compliance with Fairview's Vitrafix sub-structure system and the associated technical installation manual.

SUBSTRUCTURE & INSTALLATION

Install to Genesis Installation Manual.

For use with Vitrafix™ top hats, sarking, flashings, tapes, stainless-steel rivets. Where necessary, ensure the appropriate material and grade is used.

Ensure minimum cavity and ventilation provisions are in accordance with both the Genesis installation and NCC condensation management requirements.

Incorporate ventilated flashings as per the Genesis Installation Manual.

Incorporate fixed and floating fixed points as per the Genesis Installation Manual.

All panels installed with the grain/panel orientation running in the same direction.

ACCESSORIES & FIXINGS

Use Fairview's Vitrafix fixings and trims in accordance with the Fairview Genesis Installation Manual.

All fasteners to be stainless steel or Class 3 corrosion resistant (AS 3566).

Panel joints to be closed off with Gasket tape (EPDM) and Back Flashing ensuring you maintain a breathable facade

WARRANTY

15 - year product warranty from Fairview for the system.

Installation to be carried out by experienced façade contractor in accordance with Fairview specification.

1800 007 175
HELPPDESK@FV.COM.AU

FV.COM.AU

GENESIS / DECEMBER 2025



FAIRVIEW

DEFINING ARCHITECTURE SINCE 1969