

SPECIFICATION SHEET

FIBREFAST FACTORY-PAINTED FIBRE CEMENT



PRODUCT

Manufacturer	FVA Group (Fairview)
System	Fibrefast
Panel Type	Factory-painted fibre cement
Panel Profiles	Standard flat panel
Thickness	9mm
Finish	Factory-applied acrylic coating (prefinished only)
Colour	Alpine White, Crystal White, Granite Grey, Raven
Panel Size	1200mm x 2500mm and 1200mm x 3000mm
Joint Type	8-10mm expressed shadow line joint with EPDM gasket and aluminium backing strip
Application	Commercial, Industrial, Residential, Educational

COMPLIANCE REQUIREMENTS

Complies with NCC 2022, Volume 1	Section C – Fire Resistance Non-combustible in accordance with NCC 2022 Clause C2D10(6)(d) Tested to AS1530.3 Section F – Health and Amenity Water-permeability and heat-rain performance tested in accordance with AS2908.2 Section B – Structure Structural design in accordance with AS/NZS1170.2
Durability	50+ years design life; termite/rot/mildew resistant

SUBSTRUCTURE & INSTALLATION

Install to Fibrefast Installation Manual.

For use with Vitrafix top hats (W top hat included), sarking, flashings, tapes, wafer head screws.

Ensure minimum cavity and ventilation provisions comply with both the Fibrefast Installation Manual and NCC condensation management requirements. A minimum ventilated cavity is required behind the facade.

Install ventilated flashings, cavity barriers and moisture-management components in accordance with the Fibrefast Installation Manual.

ACCESSORIES & FIXINGS

Use Fairview Vitrafix fixings, gaskets, flashings and trims in accordance with the Fairview Fibrefast Installation Manual.

All fasteners to be stainless steel or Class 3 corrosion-resistant in accordance with AS 3566.

Panel joints to be sealed using EPDM gasket tape and back flashing to maintain a breathable ventilated facade.

WARRANTY

5-year paint warranty and 10-year panel warranty from Fairview.

Installation to be carried out by experienced façade contractor in accordance with Fairview specification.