

SPECIFICATION SHEET

SOLARA TERRACOTTA BATTEN SYSTEM



solaraTM

ARCHITECTURAL SUNSCREENS / MANUFACTURED BY FAIRVIEW

PRODUCT

Manufacturer	FVA Group (Fairview)
System	Solara
Batten Type	Terracotta Batten System
Batten Profiles	Square, Rectangular, Rectangular Wide, Louver, Lamera, Circular, Arc, Cambered
Length	300 – 1500 mm
Finish	Wide range of natural fired clay colours and glazed finishes
Colour	Refer to Solara Product Information brochure
Batten Size	Refer to Solara Product Information brochure
Application	Commercial, Residential, Mixed-used and Government

COMPLIANCE REQUIREMENTS

Complies with NCC 2022, Volume 1	Section C – Fire Resistance Non-combustible in accordance with NCC2022 – clause C2D10 (5) (g) Tested to AS1530.3 Material Performance AS 4455 / AS 4456 – Resistance to salt attack, efflorescence and lime pitting. AS 4459.3 – Water absorption. ISO 10545.2 – Tile dimensions and flatness.
Durability	Designed for long-term durability when installed in accordance with Fairview requirements.

SUBSTRUCTURE & INSTALLATION

Install to Solara Installation Manual.

System consists of extruded terracotta battens, internal structural support profiles, end-fixing brackets and screws.

Battens may be installed horizontally or vertically as specified on project drawings.

ACCESSORIES & FIXINGS

Use Fairview-approved Solara Terracotta support profiles, brackets and fixings in accordance with the Solara Installation Manual.

Ensure all fixings and support structures are suitable for project-specific structural and environmental requirements.

WARRANTY

15 - year product warranty from Fairview for the system.

Installation to be carried out by experienced façade contractor in accordance with Fairview specification.



FAIRVIEW

DEFINING ARCHITECTURE SINCE 1989