



Certificate of Conformity



This is to certify compliance of
Vitracore G2

WWW.JAS-ANZ.ORG/REGISTER

Conditions and Limitations

Product Description

The Vitracore G2 is an aluminium composite panel with a profiled aluminium core.

The Vitracore G2 is comprised of 3 layers of aluminium; an aluminium face laminate, a profiled aluminium core being the laminated material and an aluminium rear laminate.

Certificate Holder



DEFINING ARCHITECTURE SINCE 1983
ABN: 56 111 935 963
18-20 Donald St
(PO Box 277)
Lithgow NSW 2790
Ph: 61 2 6352 2355

W: www.fairviewarchitectural.com

Certification Body



CertMark International Pty Ltd

T/A CertMark Australia

ABN: 80 111 217 568

JAS-ANZ Accreditation No.

Z4450210AK

PO Box 7144, Sippy Downs Qld 4556

+61 (02) 6100 4300

www.CertMark.org

Product Purpose, Use and Application

- a. Vitracore G2 is certified for use as a decorative and weatherproof part of a walling system or as an attachment.
- b. It is suitable for Vitracore G2 to be fixed through any insulation, weatherproofing sarking-type fire resistance or acoustic material directly to the primary building element or wall frame.
- c. Vitracore G2 is tested and proven to be a non-combustible cladding system and is suitable to be used where non-combustible materials are required.
- d. Vitracore G2 is permitted to be used on buildings of Type A, B or C construction, within bushfire prone areas, on buildings fitted with or without an automatic fire sprinkler system and at any distance from a fire source feature.

Complies with the National Construction Code – Building Code of Australia 2016 Volume One

- a. Clause A0.2 (c) being a combination of compliance with the Deemed-to-Satisfy Provisions and formulating a Performance Solution which complies with the Performance Requirements.
- b. A1.1 Definitions – Non-combustible.
- c. A2.2 sub-clause (a)(ii) as evidence to support that Vitracore G2 meets the nominated Performance Requirements through a combination of the Deemed-to-Satisfy Provisions and Performance Requirements under a current Certificate of Conformity.
- d. C1.10(c)(xv) a material that does not significantly increase the hazard of fire.
- e. C1.12 - bonded laminated material deemed non-combustible.
- f. Specification C1.1 – where non-combustible material required.
- g. FP1.4 for Weatherproofing
- h. GP5.1 (including NSW and QLD GP5.1, Tas GP5.1)
 - i. G5.2 Protection (including NSW G5.2, SA G5.2, SA G5.3, Tas G5.3 and Tas G5.4)

ABCB Disclaimer

- This Certificate of Conformity is issued by an accredited certification body under arrangement with JAS-ANZ. The ABCB does not in any way warrant, guarantee or represent that the Product the subject of this Certificate of Conformity conforms to the BCA, nor accepts any liability arising out of the use of the Product. The ABCB disclaims to the extent permitted by law, all liability (including negligence) for claims of losses, expenses, damages and costs arising as a result of the use of the product(s) referred to in this Certificate.
- It is advised to check that this Certificate of Conformity is currently valid and not withdrawn, suspended or superseded by a later issue by referring to the ABCB website, www.abcb.gov.au.

		10/05/2016	10/05/2019	CMA-CM40170-I01-R02
John Thorpe	Livi Krevatin	Date of Issue	Date of Expiry	Certificate Number
CertMark International	Unrestricted Building Certifier			Revised November 2016